

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Ripcare - Shoe Repair, black

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesives, sealants
Roller application or brushing of adhesive and other coating.
Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name: Delta Distribution GmbH
Street: Am Heuberg 25
Place: D-37308 Schimberg
Telephone: 03641-5598266
e-mail: hello@delta-dist.eu
Internet: www.delta-dist.eu

1.4. Emergency telephone number:

GGIZ: +49-361-730730

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
Flammable liquid: Flam. Liq. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Hazard Statements:
Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

ethyl acetate
acetone
n-butyl acetate

Signal word: Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 2 of 13

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P235 Keep cool.
- P370+P378 In case of fire: Use ... to extinguish.
- P501 Dispose of contents/container to waste management.

Additional advice on labelling

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

polyurethane-prepolymers with stabilizers and filling materials in a mixture of organic solvents

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
67-64-1	acetone			25 - < 35 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
141-78-6	ethyl acetate			25 - < 35 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-86-4	n-butyl acetate			1 - < 5 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary. In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still.

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. Grease skin after contact

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 3 of 13

4.2. Most important symptoms and effects, both acute and delayed

Dizziness. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Where appropriate artificial ventilation.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO₂), alcohol resistant foam. Extinguishing powder, ABC powder. Atomized water. Dry sand.**Unsuitable extinguishing media**

High power water jet. High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. In case of fire and/or explosion do not breathe fumes. In case of fire may be liberated: Hydrogen chloride (HCl). Burning produces heavy smoke.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Use water spray jet to protect personnel and to cool endangered containers. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin, eyes and clothes. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/vapour/aerosol.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Vapours / aerosols must be extracted by suction immediately at point of origin. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 4 of 13

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Recommended storage temperature: 15-30 °C Ensure adequate ventilation of the storage area.

Advice on storage compatibility

Do not store together with: Oxidising agent, Pyrophoric or self-heating substances. Store packaging and combustible materials separately from one another. Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Floors should be impervious, resistant to liquids and easy to clean.

Store small packages in a suitable, robust cabinet.

7.3. Specific end use(s)

Adhesives, sealants

Roller application or brushing of adhesive and other coating.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 5 of 13

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route		Effect	Value
67-64-1	acetone			
Worker DNEL, acute	inhalation		systemic	2420 mg/m ³
Worker DNEL, long-term	inhalation		systemic	1210 mg/m ³
Worker DNEL, long-term	dermal		systemic	186 mg/kg bw/day
Consumer DNEL, long-term	dermal		systemic	62 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	200 mg/m ³
Consumer DNEL, long-term	oral		systemic	62 mg/kg bw/day
141-78-6	ethyl acetate			
Worker DNEL, long-term	inhalation		systemic	1468 mg/m ³
Worker DNEL, acute	inhalation		local	1468 mg/m ³
Worker DNEL, long-term	dermal		systemic	63 mg/kg bw/day
Worker DNEL, long-term	inhalation		local	734 mg/m ³
Consumer DNEL, acute	inhalation		systemic	734 mg/m ³
Consumer DNEL, long-term	inhalation		local	734 mg/m ³
Consumer DNEL, long-term	dermal		systemic	37 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	367 mg/m ³
Consumer DNEL, long-term	oral		systemic	4,5 mg/kg bw/day
Consumer DNEL, acute	inhalation		local	367 mg/m ³
123-86-4	n-butyl acetate			
Consumer DNEL, long-term	oral		systemic	3,4 mg/kg bw/day
Consumer DNEL, long-term	dermal		systemic	3,4 mg/kg bw/day
Worker DNEL, long-term	dermal		systemic	7 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	12 mg/m ³
Worker DNEL, long-term	inhalation		systemic	48 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 6 of 13

PNEC values

CAS No	Substance	
Environmental compartment		Value
67-64-1	acetone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Soil		29,5 mg/kg
141-78-6	ethyl acetate	
Freshwater		0,26 mg/l
Marine water		0,026 mg/l
Freshwater sediment		0,34 mg/kg
Marine sediment		0,034 mg/kg
Soil		0,22 mg/kg
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Freshwater sediment		0,981 mg/kg
Soil		0,0903 mg/kg

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work. Before starting work, apply solvent-resistant skincare preparations.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Test suitability of gloves before use.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material : 0,5 mm

Breakthrough time (maximum wearing time) : >= 1 h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 7 of 13

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection necessary at: insufficient ventilation. With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Combination filtering device (EN 14387) Use the following filter types for cleaning waste gases: A-P2

Environmental exposure controls

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste liquid
Colour:	black
Odour:	ester

Test method

pH-Value:	not applicable
-----------	----------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	56 °C DIN 53 171
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Flash point:	- 17 °C ASTM D 3278
Sustaining combustion:	No data available

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits:	2,1 vol. %
Upper explosion limits:	14,3 vol. %
Ignition temperature:	460 °C DIN 51 794

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature:	not determined
----------------------------	----------------

Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	246 hPa DIN EN 12
--------------------------------	-------------------

Vapour pressure: (at 50 °C)	814 hPa
--------------------------------	---------

Density (at 20 °C):	0,88 g/cm³ DIN 51 757
---------------------	-----------------------

Bulk density:	not applicable
---------------	----------------

Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water
-------------------	---

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 8 of 13

Solubility in other solvents

not determined

Partition coefficient:

not determined

Viscosity / dynamic:
(at 20 °C)

30000 - 32000 mPa·s DIN 53018

Viscosity / kinematic:

not determined

Flow time:

> 300 (3 mm)

Vapour density:

not determined

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

66,96 %

9.2. Other information

Solid content:

33,04 %

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

10.3. Possibility of hazardous reactions

Gas/vapour, highly flammable. Vapours can form explosive mixtures with air.

10.4. Conditions to avoidKeep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Decomposition takes place from temperatures above: > 150 °C**10.5. Incompatible materials**

Acid, concentrated. , Oxidizing agents, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**Based on available data, the classification criteria are not met.
There are no data available on the preparation/mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone				
	oral	LD50 mg/kg 5800	Ratte	RTECS	
	dermal	LD50 mg/kg 20000	Kaninchen	IUCLID	
	inhalative (4 h) vapour	LC50 76 mg/l	Ratte		
141-78-6	ethyl acetate				
	oral	LD50 mg/kg 5600	Rat		
	dermal	LD50 mg/kg 18000	Rabbit		
	inhalative (4 h) vapour	LC50 58 mg/l	Rat		
123-86-4	n-butyl acetate				
	oral	LD50 mg/kg 8800	Rat.		
	dermal	LD50 mg/kg 5000	Rabbit		
	inhalative (4 h) vapour	LC50 21 mg/l	Rat.		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

STOT-single exposure

May cause drowsiness or dizziness. (acetone; ethyl acetate)

There are no data available on the preparation/mixture itself.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Inhalation causes narcotic effects/intoxication.

Aspiration hazard

Based on available data, the classification criteria are not met.

There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Product is easily volatile. Product is slightly soluble in test vehicle. An aqueous dispersion has been tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	3300	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna	
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50	62 mg/l	96 h	Leuciscus idus	
	Acute algae toxicity	ErC50	675 mg/l	72 h	Scenedesmus subspiciatus	
	Acute crustacea toxicity	EC50	44 mg/l	48 h		

12.2. Persistence and degradability

Product is biodegradable with difficulty.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	acetone			
	OECD 301 A-F	60 BSB/CSB	28	
123-86-4	n-butyl acetate			
	DOC-Elimination	> 70 %		

12.3. Bioaccumulative potential

There are no data available on the preparation/mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone	-0,24
141-78-6	ethyl acetate	0,6
123-86-4	n-butyl acetate	1,81

BCF

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30		

12.4. Mobility in soil

There are no data available on the preparation/mixture itself.

12.5. Results of PBT and vPvB assessment

There are no data available on the preparation/mixture itself.

12.6. Other adverse effects

There are no data available on the preparation/mixture itself.

Further information

The statement is derived from the properties of the components.
Avoid release to the environment.

SECTION 13: Disposal considerations

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 11 of 13

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose according to legislation. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives (Acetone)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Special Provisions: 640H
 Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 33
 Tunnel restriction code: D/E

Other applicable information (land transport)

Additional information on classification : 2.2.3.1.4 ADR / GGVSEB

Inland waterways transport (ADN)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 12 of 13



Classification code: F1
 Special Provisions: 640H
 Limited quantity: 5 L
 Excepted quantity: E1

Other applicable information (inland waterways transport)

Additional information on classification : 2.2.3.1.4 ADR / GGVSEB

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives (Aceton)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Marine pollutant: No
 Special Provisions: 223, 955
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-D

Other applicable information (marine transport)

Additional information on classification : 2..3.2.2 IMDG-Code

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366
 IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ripcare - Shoe Repair, black

Revision date: 12.04.2018

Product code: 021

Page 13 of 13

EU regulatory information

2010/75/EU (VOC): 100 % (880 g/l)

2004/42/EC (VOC): 100 % (880 g/l)

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,7,9.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)